



Printer Accessories

ACP01: Thermal, handheld printer



- User-friendly portable printer with single-handed paper-load system.
- High speed and high quality printing mechanism with superb text quality.
- Suitable for the F132 and N413 batch controllers.

Specifications	
Data Input	RS-232 Serial
Data Buffer	20 KB
Baud Rate	Up to 57,600 (9600 Default)
Print Method	Fixed head thermal mechanism
Print Width	48 mm
Dot spacing	8 dots/mm (vertical and horizontal)
Dots per line	384
Font (dots)	7 x 24 / 10 x 24
Paper roll length	16 m
Dimensions	47 x 92 x 108 mm (H x W x L)
Weight	330 gr (including battery and full roll of paper)
Temperature	Ambient 0 - 50°C (32 - 122°F)

Ordering information	
ACP01	Ap 1300 - Thermal portable printer (incl. cables and battery charger).

ACP02 / ACP03: Thermal panel mount printer



- Robust design which is suitable for both vertical and horizontal panel mounting.
- Increased usability with expanded reporting for 'head up' and 'paper out' errors.
- Suitable for the F132 and N413 batch controllers.

Specifications	
Data Input	RS-232 Serial
Data Buffer	10 KB
Baud Rate	Up to 115,200 Baud (9600 Default)
Print Method	Fixed head thermal mechanism
Print Width	48 mm
Dot spacing	8 dots/mm (vertical and horizontal)
Dots per line	384
Font (dots)	8 x 16 / 7 x 24 / 10 x 24
Paper roll length	12 m
Dimensions	80 x 83 x 52mm (H x W x D)
Panel cut-out	75 x 75 mm (W x D)
Weight	110 gr (without paper)
Temperature	Ambient 0 - 50°C (32 - 122°F)

Ordering information	
ACP02	Ap 1400 - Thermal panel printer with standard 3.5V DC to 8.5V DC power supply (incl. cables).
ACP03	Ap 1400 - Thermal panel printer with external 100 - 240V AC power supply (incl. cables).